

WISCO 925/925W BLOWER MOTOR REPLACEMENT KIT
KIT #0018644SK

TOOLS NEEDED:

Phillips Screwdriver
11/32" Nut Driver
Wire Cutters

PARTS INCLUDED:

Blower Motor Assy - part #0018644
(2) Wire Ties

Installation Instructions:

- 1) Unplug unit from outlet and let cool
- 2) Unscrew top cover. Set cover and screws aside.
- 3) Remove (1) hex nut from the end of the air chamber on the blower motor side. Remove screws from the cover of the air chamber. Set cover and screws aside.
- 4) Spread apart the walls of the air chamber near the blower motor. Pull motor assembly up and away from the air chamber mounting stud. Snip the wire tie holding the (2) wires coming from the blower motor assembly.
- 5) Attach replacement blower motor assembly. Make sure the mounting hole from the blower motor assembly is placed down around the mounting stud and the blower motor assembly flanges are on the inside of the air chamber flanges.
- 6) Unplug old blower motor wires from the terminal block. Discard old blower motor. Plug replacement blower motor into the exact same (2) terminal block locations.
- 7) Using the wire ties, tie any wires away from any moving parts and heat sources. Reattach blower mounting nut and air chamber cover. Tighten all fasteners securely. Reattach top cover and tighten all fasteners securely.
- 8) Plug unit in. Unit is now ready for operation.

FS140080
Rev. 02-15-12
Sales Drive/FS#