



**WISCO INDUSTRIES, INC.**

OREGON, WISCONSIN 53575 • TELEPHONE (608) 835-3106  
FAX (608) 835-7399

## **608 CONVECTION OVEN THERMOSTAT REPLACEMENT**

**REQUIRED TOOLS:** Phillips Screw Driver  
Flat Head Screw Driver (small head)  
Flat Head Screw Driver (medium head)

- 1) Unplug unit.
- 2) Remove Shelves and Support Rack from Inner Cavity. DO NOT REMOVE the (2) Finger Screws right and left near top of Inner Cavity. Flex the Support Rack around the screw heads, once the front of the rack has cleared the screws gently flex the rack into a parallelogram with the right side back and remove.
- 3) Loosen the (2) Finger screws holding the Thermostat Bulb Guard in place just enough to free the Capulary Bulb.
- 4) Remove the Outer Housing by extracting the (8) screws on the bottom (4 per side), (13) screws on the back, and loosening the (4) black screws across the top of the front panel. With the oven facing you remove the Outer Enclosure lifting the left side out and up first and then the right. Be sure to flex the right side out far enough to allow the internal Shroud to clear the Cooling Fan.
- 5) Remove the Back Panel by extracting the (2) recessed screws located just off center near top and bottom of the Back Panel, then extract the (5) screws near the base.
- 6) Remove the Capulary line through the back on the Inner Cavity.
- 7) Remove the Thermostat Knob by loosening the set screw.
- 8) Remove (2) screws anchoring the Thermostat to the Front Panel.
- 9) Transfer wires to the new Thermostat and reverse this process.

FS140009

## IMPORTANT REASSEMBLY NOTES

- 1) Space the Thermostat Knob about 1/8" off the Front Panel (it moves in and out as it rotates).
- 2) Re-anchor wires clear of Fan Blades with wire ties.
- 3) When repositioning the Back Panel, make sure the (2) exhaust ports are properly aligned with the Back Panel holes.
- 4) Check that the entire front offset on the Outer Enclosure is between the primary and secondary Front Panels, not behind both of them.
- 5) Put downward pressure on the front of the Outer Enclosure when tightening the (4) black screws located along the upper Front Panel.

If you have any questions please feel free to call us.

Thank You